



# SPECIFICATION CONTROL DRAWING

## 3. MECHANICAL

### CAPTIVATION-CENTER CONTACT

- MIN. AXIAL FORCE \_\_\_\_\_ 1.5 LBS.
- MIN. RADIAL TORQUE \_\_\_\_\_ N/A

RADIAL MISALIGNMENT \_\_\_\_\_ .010 MIN.  
AXIAL MISALIGNMENT \_\_\_\_\_ .000/.010

### CONNECTOR DURABILITY (MIN. MATING)

- A.) FULL DETENT \_\_\_\_\_ 100
- B.) LIMITED DETENT \_\_\_\_\_ 500
- C.) SMOOTH BORE \_\_\_\_\_ 1000

## 4. ENVIRONMENTAL

THERMAL SHOCK \_\_\_\_\_ MIL-STD-202, METHOD 107, COND. B ( HIGH TEMP. +165°c )  
SHOCK \_\_\_\_\_ MIL-STD-202, METHOD 213, COND. I (100 G's)  
VIBRATION \_\_\_\_\_ MIL-STD-202, METHOD 204, COND. D (20 G's)  
MOISTURE RESISTANCE \_\_\_\_\_ MIL-STD-202, METHOD 106, LESS STEP 7b,  
1000 MEGOHMS MINIMUM WITHIN 5 MINUTES.  
CORONA (70,000 FEET) \_\_\_\_\_ 190 VRMS  
RF HIGH POTENTIAL MIN. VOLTS \_\_\_\_\_ 325 VRMS @ SEA LEVEL, FREQ. 5 MHz.  
VIBRATION, RANDOM \_\_\_\_\_ MIL-STD 202, METHOD 214, TEST CONDITION F

## 5. MATERIAL

CONNECTOR BODY AND CENTER CONTACT \_\_\_\_\_ BERYLLIUM COPPER PER ASTM-B-196/B, 196M-03, COPPER  
ALLOY No. UNS-C17300, TEMPER TD04.  
INSULATOR \_\_\_\_\_ TEFLON PER ASTM-D-1710-02, TYPE 1, GRADE 1, CLASS B.

## 6. FINISH

CONNECTOR BODY AND CENTER CONTACT \_\_\_\_\_ GOLD PER ASTM-B-488, TYPE I, CODE C, CLASS 1.25  
(.000050-.000100 THK.) OVER NICKEL PER SAE-AMS-QQ-N-290,  
CLASS 1 (.000100 MIN. THK.) OVER COPPER PER AMS-2418,  
(.000040 MIN. THK.)  
INSULATOR \_\_\_\_\_ N/A