


SPECIFICATION CONTROL DRAWING




1. MATING INTERFACE DIMENSIONS PER MIL-STD-348A, (Fig. 310.1)

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 3.0 GHz.
VSWR (MAX.) *	1.05 + .005 x FGHz.
INSERTION LOSS (dB MAX.) *	.03 dB x $\sqrt{\text{FGHz}}$.
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	250
RF LEAKAGE (MIN. dB DOWN)	100 dB - FGHz.
TEMPERATURE RATING (DEGREES CENTIGRADE)	-65 ° c TO +165 ° c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	750
INSULATION RESISTANCE (MIN. MEGOHMS)	5,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	3.0
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

* TERMINATED IN A 50 OHM LOAD

REV.	DCN NO.	DATE	APP.	DIMENSIONS ARE IN INCHES TOLERANCES			 HAVERHILL, MA. 01835
AA	04-1895	7/29/04	DC	DECIMALS .X ± .030 .XX ± .010 .XXX ± .005	FRACTIONAL ±/64	ANGULAR X° ± 1'0" X° X' ± 15"	
				SURFACE ROUGHNESS 63 √ MIL-STD 10.			TITLE SMA, PLUG WITH CENTER CONTACT TO RG-316 CABLE DIRECT SOLDER ATTACHMENT
				DRAWN DC	DATE 7/29/04		
				APPROVED DC	DATE 7/29/04		
				CODE IDENT. 2J899	SHEET 1 OF 2	DWG. NO. 9800-1620-6246	

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION-CENTER CONTACT

- MIN. AXIAL FORCE _____ N/A
- MIN. RADIAL TORQUE _____ N/A

CENTER CONTACT AXIAL FORCES

- INSERTION (MAX. OUNCES) _____ N/A
- WITHDRAWAL (MIN. OUNCES) _____ N/A

CONNECTOR ENGAGEMENT/DISENGAGEMENT (MAX. IN. LBS.) _____ 2.0

CONNECTOR DURABILITY (MIN. CYCLES) _____ 500

RECOMMENDED MATING TORQUE _____ 7 - 10 IN. LBS.

4. ENVIRONMENTAL

TEMPERATURE CYCLING _____ MIL-STD-202, METHOD 102, COND. C (-65 ° c TO + 200 ° c)

SHOCK _____ MIL-STD-202, METHOD 213, COND. I (100 G's)

VIBRATION _____ MIL-STD-202, METHOD 204, COND. D (20 G's)

MOISTURE RESISTANCE _____ MIL-STD-202, METHOD 106, LESS STEP 7b

CORROSION _____ MIL-STD-202, METHOD 101, COND. B (48 HOURS)

BAROMETRIC PRESSURE (ALTITUDE) _____ MIL-STD-202, METHOD 105, COND. C (70,000 FT.) (375 VRMS)

5. MATERIAL

SHRINK TUBING _____ MIL-I-23053/4-103-0

BODY AND COUPLING NUT _____ STAINLESS STEEL PER ASTM A 581, TYPE 303, COND. A.

CONTACT AND RETAINING RING _____ BERYLLIUM COPPER PER ASTM B196-90, COPPER ALLOY
No. UNS C17300, TEMPER TD04.

INSULATOR _____ TEFLON PER ASTM D 4894-91.

GASKET _____ ETHYLENE PROPYLENE

6. FINISH

BODY _____ GOLD PER MIL-G-45204, TYPE I, GRADE C, CLASS 1
(.000050 MINIMUM THICKNESS) OVER NICKEL PER
QQ-N-290, CLASS 1 (.000150 MINIMUM THICKNESS) OVER
COPPER PER MIL-C-14550 (.000010 MINIMUM THICKNESS).

COUPLING NUT _____ PASSIVATE PER QQ-P-35A, TYPE I.

CONTACT _____ GOLD PER MIL-G-45204, TYPE II, GRADE C, CLASS 2
(.000100 MINIMUM THICKNESS) OVER NICKEL PER
QQ-N-290, CLASS 1 (.000100 MINIMUM THICKNESS) OVER
COPPER PER MIL-C-14550 (.000010 MINIMUM THICKNESS).

INSULATOR, GASKET AND SHRINK TUBING _____ N/A