


# SPECIFICATION CONTROL DRAWING




1. MATING INTERFACE DIMENSIONS FOR PLUG PER MIL-STD-348 (Fig. 310-1) AND DYNAWAVE MD-98.

## 2. ELECTRICAL

FREQUENCY RANGE GHz	_____	DC TO 34.0 GHz.
VSWR (MAX) *	_____	1.05 + .005 x FGHz.
INSERTION LOSS (dB MAX) *	_____	.03 dB x $\sqrt{\text{FGHz}}$ .
NOMINAL IMPEDANCE (OHMS)	_____	50
VOLTAGE RATING (MAX. VRMS)	_____	335
RF LEAKAGE (MIN. dB DOWN)	_____	100 dB - FGHz.
TEMPERATURE RATING (DEGREES CENTIGRADE)	_____	-65 ° c TO +165 ° c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	_____	1,500
INSULATION RESISTANCE (MIN. MEGOHMS)	_____	10,000
CONTACT RESISTANCE		
• CENTER CONTACT (MAX. MILLIOHMS)	_____	3.0
• OUTER CONTACT (MAX. MILLIOHMS)	_____	2.0

\* TERMINATED IN A 50 OHM LOAD

REV.	DCN NO.	DATE	APP.	DIMENSIONS ARE IN INCHES TOLERANCES			 GEORGETOWN MA. 01833
				DECIMALS	FRACTIONAL	ANGULAR	
AA	06-1351	3/17/06	TS	.X + .030 .XX ± .010 .XXX ± .005	± 1/64	X ° ± 1' 0" X ° X ± 15'	TITLE SMA, PLUG TO .141 S.R. CABLE DIRECT SOLDER ATTACHMENT (NO CONTACT)
				SURFACE ROUGHNESS 63 √ MIL-STD 10.			
				DRAWN	TS	DATE 3/17/06	
				APPROVED	DC	DATE 3/17/06	
				CODE IDENT.			DWG. NO. 9800-4426-6240
				2J899	SHEET 1 OF 2		

# SPECIFICATION CONTROL DRAWING

## 3. MECHANICAL

### CAPTIVATION-CENTER CONTACT

- MIN. AXIAL FORCE \_\_\_\_\_ N/A
- MIN. RADIAL TORQUE \_\_\_\_\_ N/A

### CENTER CONTACT AXIAL FORCES

- INSERTION (MAX. OUNCES) \_\_\_\_\_ N/A
- WITHDRAWAL (MIN. OUNCES) \_\_\_\_\_ N/A

CONNECTOR ENGAGEMENT/DISENGAGEMENT (MAX. IN. LBS.) \_\_\_\_\_ 2.0

CONNECTOR DURABILITY (MIN. CYCLES) \_\_\_\_\_ 500

RECOMMENDED MATING TORQUE \_\_\_\_\_ 7 - 10 IN. LBS.

## 4. ENVIRONMENTAL

TEMPERATURE CYCLING \_\_\_\_\_ MIL-STD-202, METHOD 102, COND. C ( -65 ° c TO + 200 ° c )

SHOCK \_\_\_\_\_ MIL-STD-202, METHOD 213, COND. I (100 G's)

VIBRATION \_\_\_\_\_ MIL-STD-202, METHOD 204, COND. D (20 G's)

MOISTURE RESISTANCE \_\_\_\_\_ MIL-STD-202, METHOD 106, LESS STEP 7b

CORROSION \_\_\_\_\_ MIL-STD-202, METHOD 101, COND. B (48 HOURS)

BAROMETRIC PRESSURE (ALTITUDE) \_\_\_\_\_ MIL-STD-202, METHOD 105, COND. C ( 70,000 FT. ) ( 375 VRMS )

## 5. MATERIAL

CONNECTOR BODY AND COUPLING NUT \_\_\_\_\_ STAINLESS STEEL PER ASTM A 582, TYPE 303, COND. A.

RETAINING RING \_\_\_\_\_ BERYLLIUM COPPER PER ASTM B196-90, COPPER ALLOY No. UNS C17300

GASKET \_\_\_\_\_ SILICONE RUBBER PER ZZ-R-765, CLASS IIB, GRADE 50 OR 60.

## 6. FINISH

CONNECTOR BODY \_\_\_\_\_ GOLD PER ATSM B 488, TYPE I, CODE C, CLASS 1.25  
(.000050 MIN. THK.) OVER NICKEL PER QQ-N-290, CLASS 1  
(.000150 MIN. THK.) OVER NICKEL (WOODS OR WATTS),  
(.000010 MIN. THK.).

COUPLING NUT \_\_\_\_\_ PASSIVATE PER AMS QQ-P-35C, TYPE V2

RETAINING RING AND GASKET \_\_\_\_\_ N/A