


SPECIFICATION CONTROL DRAWING




1. MATING INTERFACE DIMENSIONS Per MIL-STD-348 Fig. 310.2 (SMA JACK).

2. ELECTRICAL

| | | |
|---|-------|--------------------|
| FREQUENCY RANGE GHz | _____ | DC TO 26.5 GHz |
| VSWR (MAX) * | _____ | 1.05 + .006 x FGHz |
| INSERTION LOSS (dB MAX) * | _____ | .05 dB x √FGHz |
| NOMINAL IMPEDANCE (OHMS) | _____ | 50 |
| VOLTAGE RATING (MAX. VRMS) | _____ | 250 |
| RF LEAKAGE (MIN. dB DOWN) | _____ | -100 dB - FGHz |
| TEMPERATURE RATING (DEGREES CENTIGRADE) | _____ | -65°C TO + 165°C |
| DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS) | _____ | 750 |
| INSULATION RESISTANCE (MIN. MEGOHMS) | _____ | 5,000 |
| CONTACT RESISTANCE | | |
| • CENTER CONTACT (MAX. MILLIOHMS) | _____ | 6.0 |
| • OUTER CONTACT (MAX. MILLIOHMS) | _____ | 2.0 |

* TERMINATED IN A 50 OHM LOAD

RoHS
COMPLIANT

| REV. | DCN NO. | DATE | APP. | DIMENSIONS ARE IN INCHES TOLERANCES | | |  HAVERHILL, MA 01835 |
|------|---------|---------|------|--|----------------------|---|--|
| AA | 13-1450 | 3/29/13 | DC | DECIMALS .X ± .030 .XX ± .010 .XXX ± .005 | FRACTIONAL ± 1/64 | ANGULAR X ° ± 1° 0' X ° X' ± 15' | |
| | | | | DRAWN DC | DATE 3/29/13 | TITLE SMA, JACK SCREW-IN MIC. PACKAGE ACCEPTS Ø.021/.017 PIN | |
| | | | | APPROVED DC | DATE 3/29/13 | | |
| | | | | CODE IDENT. 2J899 | SHEET 1 OF 2 | | |
| | | | | | | DWG. NO. 9930-0881-6202 | |

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION-CENTER CONTACT

MAX AXIAL FORCE _____ 6.0 LBS.

MAX RADIAL TORQUE _____ N/A

CENTER CONTACT AXIAL FORCES

● INSERTION (MAX OUNCES) _____ INTERFACE 48.0, *REAR 32.0*

● WITHDRAWAL (MIN. OUNCES) _____ INTERFACE 2.0, *REAR 1.0*

CONNECTOR ENGAGEMENT/DISENGAGEMENT (MAX IN. LBS.) — 2.0

CONNECTOR DURABILITY (MIN. CYCLES) _____ 500

RECOMMENDED MATING TORQUE _____ 7 - 10 IN. LBS.

RECOMMENDED MOUNTING TORQUE _____ 27 - 30 IN. LBS.

RECOMMENDED TORQUE TOOL _____ 99-TORQUE-30

* WHEN TESTED TO .018 ±.001 OR .020 ±.001 FEED THRU SIZE *

4. ENVIRONMENTAL

TEMPERATURE CYCLING _____ MIL-STD-202, METHOD 102, COND. C (-65° c TO + 165° c)

SHOCK _____ MIL-STD-202, METHOD 213, COND. I (100 G's)

VIBRATION _____ MIL-STD-202, METHOD 204, COND. D (20 G's)

MOISTURE RESISTANCE _____ MIL-STD-202, METHOD 106, LESS STEP 7b

CORROSION _____ MIL-STD-202, METHOD 101, COND. B (48 HOURS)

BAROMETRIC PRESSURE (ALTITUDE) _____ MIL-STD-202, METHOD 105, COND. C (70,000 FT.) (190 VRMS)

5. MATERIAL

BODY _____ STAINLESS STEEL PER ASTM-A-582, TYPE 303, COND. A

CONTACT _____ BERYLLIUM COPPER PER ASTM B196/B 196-M03, COPPER ALLOY
No. UNS-C17300, TEMPER TD04.

INSULATOR _____ TEFLON PER ASTM-D-1710-02, TYPE 1, GRADE 1, CLASS B.

6. FINISH

BODY _____ PASSIVATE PER AMS-2700, TYPE 2, CLASS 4.

CONTACT _____ GOLD PER ASTM-B-488, TYPE I, CODE C, CLASS 1.27
(.000050 MIN. THK.) OVER NICKEL per QQ-N-290 CLASS 1
(.000050 MIN. THK.) OVER COPPER per AMS-2418
(.000010 MIN. THK.).

INSULATOR _____ N/A