INFORMATION CONTAINED WITHIN THIS DYNAWAVE CABLE INC. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF DYNAWAVE CABLE INC. HAVERHILL, MA. 01835

SPECIFICATION CONTROL DRAWING

DWG. NO. SMSM-B1RH-XXX

TABLE

PART NUMBER	LENGTH	+ / -	LOSS dB
SMSM-B1RH-120	120"	1.20"	-4.75
SMSM-B1RH-118	118"	1.18"	-4.68
SMSM-B1RH-108	108"	1.08"	-4.31
SMSM-B1RH-098	98"	.98"	-3.95
SMSM-B1RH-096	96"	.96"	-3.87
SMSM-B1RH-084	84"	.84"	-3.44
SMSM-B1RH-079	79"	.79"	-3.25
SMSM-B1RH-072	72"	.72"	-3.00
SMSM-B1RH-060	60"	.60"	-2.56
SMSM-B1RH-059	59"	.59"	-2.52
SMSM-B1RH-054	54"	.54"	-2.34
SMSM-B1RH-048	48"	.48"	-2.12
SMSM-B1RH-042	42"	.42"	-1.90
SMSM-B1RH-040	40"	.40"	-1.83
SMSM-B1RH-039	39"	.39"	-1.79
SMSM-B1RH-036	36"	.36"	-1.68
SMSM-B1RH-030	30"	.30"	-1.46
SMSM-B1RH-024	24"	.25"	-1.24
SMSM-B1RH-018	18"	.25"	-1.02
SMSM-B1RH-012	12"	.25"	-0.80





CONFIDENTIAL

NOTES:
1) CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
2) TESTED 100%, DC - 26.0 GHz., VSWR 1.35:1, LOSS -X.XXdB (SEE TABLE).
3) TEST DATA SUPPLIED WITH ASSEMBLY.

ITEM	QTY	PART NUMBER	DESCRIPTION
5	1	PDL-2	PANDUIT LABEL (BARCODE)
4	A/R	B2(3X)12/4	SUMITUBE, BLACK
3	A/R	M23053/4-303-0	TUBING, ADHESIVE
2	A/R	DF226	Ø.220 LOW LOSS CABLE
1	2	9800-226H-6240	SMA(P)STR, SO/CL, DF226

REV.	DCN NUMBER	DATE	APP.
AA	15-2340	9/24/15	DC

REV. 10/13

PACKAGE MARKING

CUST. CAGE: N/A
CUST. P/N: N/A
DYNA. CAGE: 6DZL5
DYNA. P/N: SMSM-B1RH-XXX
LOT NO.: XXXXXX
DATE CODE: XXXX

TOLERANCES

DECIMALS	FRACTIONAL	DEGREES
.X ±.250 .XX ±.125 .XXX ±.060	± 1/16"	X°±1°O' X°X' ±15'

A. DIMENSIONS ARE IN INCHES.

CUSTOMER

CATALOG ITEM

DRAWN: DC DATE: 9/3/15

APPROVED: DC DATE: 9/3/15

SCALE	CODE IDENT	SHEET
N/A	6DZL5	1 of 1

dynawave® CABLE INCORPORATED
Haverhill, MA. 01835

TITLE

DynaFlex® ASSEMBLY

DRAWING NO. SMSM-B1RH-XXX