INFORMATION CONTAINED WITHIN THIS DYNAWAVE CABLE INC. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF DYNAWAVE CABLE INC. HAVERHILL, MA. 01835

SPECIFICATION CONTROL DRAWING

DWG. NO. TMTM-A9PH-XXX

TABLE

PART NUMBER	LENGTH	+ / -	LOSS dB
TMTM-A9PH-120	120"	1.20"	-2.53
TMTM-A9PH-118	118"	1.18"	-2.49
TMTM-A9PH-108	108"	1.08"	-2.30
TMTM-A9PH-098	98"	.98"	-2.11
TMTM-A9PH-096	96"	.96"	-2.07
TMTM-A9PH-084	84"	.84"	-1.85
TMTM-A9PH-079	79"	.79"	-1.76
TMTM-A9PH-072	72"	.72"	-1.62
TMTM-A9PH-060	60"	.60"	-1.40
TMTM-A9PH-059	59"	.59"	-1.38
TMTM-A9PH-054	54"	.54"	-1.29
TMTM-A9PH-048	48"	.48"	-1.17
TMTM-A9PH-042	42"	.42"	-1.06
TMTM-A9PH-040	40"	.40"	-1.02
TMTM-A9PH-039	39"	.39"	-1.01
TMTM-A9PH-036	36"	.36"	-0.95
TMTM-A9PH-030	30"	.30"	-0.84
TMTM-A9PH-024	24"	.25"	-0.72
TMTM-A9PH-018	18"	.25"	-0.61
TMTM-A9PH-012	12"	.25"	-0.50





CONFIDENTIAL

NOTES:
1) CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
2) TESTED 100%, DC - 18.0 GHz., VSWR 1.30:1, LOSS -X.XXdB (SEE TABLE).
3) TEST DATA SUPPLIED WITH ASSEMBLY.

ITEM	QTY	PART NUMBER	DESCRIPTION
5	1	PDL-2	PANDUIT LABEL (BARCODE)
4	A/R	B2(3X)18/9	SUMITUBE, BLACK
3	A/R	M23053/4-303-0	TUBING, ADHESIVE
2	A/R	DF218	Ø.295 LOW LOSS CABLE
1	2	8400-218H-6240	TNC(P)STR, SO/CL, DF218

REV.	DCN NUMBER	DATE	APP.
AA	15-2320	9/18//15	DC

REV. 10/13

PACKAGE MARKING

CUST. CAGE: N/A
CUST. P/N: N/A
DYNA. CAGE: 6DZL5
DYNA. P/N: TMTM-A9PH-XXX
LOT NO.: XXXXXX
DATE CODE: XXXX

TOLERANCES

DECIMALS	FRACTIONAL	DEGREES
.X ±.250 .XX ±.125 .XXX ±.060	± 1/16"	X°±1°O' X°X' ±15'

A. DIMENSIONS ARE IN INCHES.

CUSTOMER

CATALOG ITEM

DRAWN: DC DATE: 9/3/15

APPROVED: DC DATE: 9/3/15

SCALE	CODE IDENT	SHEET
N/A	6DZL5	1 of 1

dynawave®
CABLE INCORPORATED
Haverhill, MA. 01835

TITLE

DynaFlex® ASSEMBLY

DRAWING NO. TMTM-A9PH-XXX