SPECIFICATION CONTROL DRAWING



CONFIDENTIAL

1. MATING INTERFACE DIMENSIONS Per CECC 22220

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 6.0 GHz.
VSWR (MAX.) ❋	1.15 + .025 x FGHz
INSERTION LOSS (dB MAX.) ❋	.10 dB x $\sqrt{FGHz}$
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	.335
RF LEAKAGE (MIN. dB DOWN)	−65 dB − FGHz
TEMPERATURE RATING (DEGREES CENTIGRADE)	−65°c TO + 165°c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	1,000
INSULATION RESISTANCE (MIN. MEGOHMS)	5,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	5.0
• OUTER CONTACT (MAX. MILLIOHMS)	1.0

❋ TERMINATED IN A 50 OHM LOAD

REV.	DCN NO.	DATE	APP.
AA	07−1866	8/29/07	DC
AA	07−1869	8/30/07	DC

DIMENSIONS ARE IN INCHES
TOLERANCES

DECIMALS	FRACTIONAL	ANGULAR
.X ±.030 .XX ±.010 .XXX ±.005	± 1/64	X °±1°0' X ° X' ± 15'

dynawave INCORPORATED
HAVERHILL, MA 01835

DRAWN DC DATE 8/29/07

APPROVED DC DATE 8/29/07

TITLE
MCX JACK
2 HOLE FLANGE
ACCEPTS Ø.016/.011 PIN

CODE IDENT. 2J899

SHEET 1 OF 2

DWG. NO. 1652−0081−6215

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT

MAX. AXIAL FORCE	3.5 LBS.
MAX. RADIAL TORQUE	N/A

CENTER CONTACT AXIAL FORCES

● INSERTION (MAX. OUNCES)	INTERFACE 32.0, REAR 32.0
● WITHDRAWAL (MIN. OUNCES)	INTERFACE 2.0, REAR 1.0
CONNECTOR ENGAGEMENT/DISENGAGEMENT (MAX. LBS.)	N/A
CONNECTOR DURABILITY (MIN. CYCLES)	500
RECOMMENDED MATING TORQUE	N/A

CONFIDENTIAL

4. ENVIRONMENTAL

TEMPERATURE CYCLING	MIL–STD–202, METHOD 102, COND. C (–65° c TO + 165° c)
SHOCK	MIL–STD–202, METHOD 213, COND. I (100 G's)
VIBRATION	MIL–STD–202, METHOD 204, COND. D (20 G's)
MOISTURE RESISTANCE	MIL–STD–202, METHOD 106, LESS STEP 7b
CORROSION	MIL–STD–202, METHOD 101, COND. B (48 HOURS)
BAROMETRIC PRESSURE (ALTITUDE)	MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (250 VRMS)

5. MATERIAL

BODY	STAINLESS STEEL PER ASTM–A–582, TYPE 303, COND. A
CONTACT	BERYLLIUM COPPER PER ASTM–B–196–90, COPPER ALLOY No. UNS–C17300, TEMPER TD04.
INSULATOR	TEFLON PER ASTM–D–1710.

6. FINISH

BODY	PASSIVATE PER AMS QQ–P–35, TYPE 2.
CONTACT	GOLD PER ASTM–B–488, TYPE I, CODE C, CLASS 2.5 (.000100 MIN. THK.) OVER NICKEL per QQ–N–290 (.000050 MIN. THK.) OVER COPPER per MIL–C–14550 (.000010 MIN. THK.)
INSULATOR	N/A