SPECIFICATION CONTROL DRAWING



CONFIDENTIAL

1. MATING INTERFACE DIMENSIONS PER DYNAWAVE SPEC. MD-21-7 (SMP PLUG) AND MIL-STD-348A-326.3

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 39.0 GHz.
VSWR (MAX.) ❁	1.02 + .003 x FGHz.
INSERTION LOSS (dB MAX.) ❁	.045 dB x $\sqrt{\text{FGHz}}$.
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	250
RF LEAKAGE (MIN. dB DOWN)	N/A
TEMPERATURE RATING (DEGREES CENTIGRADE)	−65 ° c TO +165 ° c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	750
INSULATION RESISTANCE (MIN. MEGOHMS)	10,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	10.0
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

❁ TERMINATED IN A 50 OHM LOAD

REV.	DCN NO.	DATE	APP.
AA	03-2093	8/26/03	DC
AB	05-1065	1/14/05	TS

DIMENSIONS ARE IN INCHES
TOLERANCES
DECIMALS: .X ±.030, .XX ±.010, .XXX ±.005
FRACTIONAL: ±1/64
ANGULAR: X° ±1°, X' ±15'
SURFACE ROUGHNESS 63 √ MIL-STD 10.

dynawave INCORPORATED
HAVERHILL, MA. 01835

DRAWN DC DATE 8/26/03

APPROVED DATE

TITLE SMP, PLUG (LIMITED DETENT) HERMETICALLY SEALED SHROUD SOLDER MOUNT

CODE IDENT. 2J899

SHEET 1 OF 2

DWG. NO. 2147-0434-7440

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT

- MIN. AXIAL FORCE ——— 4.5 LBS.
- MIN. RADIAL TORQUE ——— 2.5 IN. OZ.

CONNECTOR ENGAGEMENT FORCES

- INSERTION (MAX. OUNCES) ——— 10.0 LBS.
- WITHDRAWAL (MIN. OUNCES) ——— 5.0 LBS.

CONNECTOR DURABILITY (MIN. MATING) ——— N/A

4. ENVIRONMENTAL

TEMPERATURE CYCLING	MIL–STD–202, METHOD 102, COND. C (–65 °c TO + 200 °c)
SHOCK	MIL–STD–202, METHOD 213, COND. I (100 G's)
VIBRATION	MIL–STD–202, METHOD 204, COND. D (20 G's)
MOISTURE RESISTANCE	MIL–STD–202, METHOD 106, LESS STEP 7b
CORROSION	MIL–STD–202, METHOD 101, COND. B (48 HOURS)
BAROMETRIC PRESSURE (ALTITUDE)	MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (190 VRMS)
HERMETICITY	1×10^{-8} cc/SEC.

CONFIDENTIAL

5. MATERIAL

CONNECTOR BODY AND GLASS PIN	KOVAR PER MIL–I–23011
GLASS	CORNING 7070

6. FINISH

CONNECTOR BODY AND GLASS PIN	GOLD PER MIL–G–45204,TYPE III,GRADE A, CLASS 1 (.000050 MIN. THK.) OVER NICKEL PER MIL–P–27416 (.000100/.000150 THK.) OVER NICKEL (WOODS OR WATTS),(.00001 MIN. THK.)
GLASS	N/A