SPECIFICATION CONTROL DRAWING



CONFIDENTIAL

1. MATING INTERFACE DIMENSIONS PER MIL-STD-348A Fig. 326.3 (SMP, LIMITED DETENT))

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 39.0 GHz.
VSWR (MAX.) ❋	1.02 + .003 x FGHz.
INSERTION LOSS (dB MAX.) ❋	.045 dB x $\sqrt{\text{FGHz}}$.
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	250
RF LEAKAGE (MIN. dB DOWN)	N/A
TEMPERATURE RATING (DEGREES CENTIGRADE)	−65 ° c TO +165 ° c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	750
INSULATION RESISTANCE (MIN. MEGOHMS)	10,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	10.0
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

❋ TERMINATED IN A 50 OHM LOAD

RoHS
COMPLIANT

REV.	DCN NO.	DATE	APP.
AA	11-2105	12/15/11	TS

DIMENSIONS ARE IN INCHES
TOLERANCES
DECIMALS: .X ±.030, .XX ±.010, .XXX ±.005
FRACTIONAL: ±1/64
ANGULAR: X ° ±1 °0', X ° X' ± 15'
SURFACE ROUGHNESS 63 √ MIL-STD 10.

dynawave INCORPORATED
HAVERHILL, MA. 01835

DRAWN TS DATE 12/15/11

APPROVED DC DATE 12/15/11

TITLE SMP, PLUG
(LIMITED DETENT)
HERMETICALLY SEALED SHROUD
SOLDER MOUNT

CODE IDENT. 2J899

SHEET 1 OF 2

DWG. NO. 2147-0435-7409

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT
- MIN. AXIAL FORCE ——— 4.5 LBS.
- MIN. RADIAL TORQUE ——— N/A

CONNECTOR ENGAGEMENT FORCES
- INSERTION (MAX. OUNCES) ——— 10.0 LBS.
- WITHDRAWAL (MIN. OUNCES) ——— 2.0 LBS.

CONNECTOR DURABILITY (MIN. MATING) ——— 250

4. ENVIRONMENTAL

TEMPERATURE CYCLING	MIL–STD–202, METHOD 102, COND. C (–65 ° c TO + 200 °c)
SHOCK	MIL–STD–202, METHOD 213, COND. I (100 G's)
VIBRATION	MIL–STD–202, METHOD 204, COND. D (20 G's)
MOISTURE RESISTANCE	MIL–STD–202, METHOD 106, LESS STEP 7b
CORROSION	MIL–STD–202, METHOD 101, COND. B (48 HOURS)
BAROMETRIC PRESSURE (ALTITUDE)	MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (190 VRMS)
HERMETICITY	1×10^{-8} cc/SEC.

CONFIDENTIAL

5. MATERIAL

CONNECTOR BODY AND GLASS PIN	KOVAR PER MIL–I–23011
GLASS	CORNING 7070

6. FINISH

CONNECTOR BODY AND GLASS PIN	GOLD PER ASTM B 488, TPYE 1, CODE C, CLASS 1.25 (.000050 MIN. THK.) OVER NICKEL PER SAE AMS QQ–N–290, CLASS 1 (.000050 MIN. THK.) OVER COPPER PER AMS 2418 (.000010 MIN. THK.)
GLASS	N/A