SPECIFICATION CONTROL DRAWING



CONFIDENTIAL

1. MATING INTERFACE DIMENSIONS PER MIL-STD-348A-326.2 (SMP, PLUG, FULL DETENT)

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 26.5 GHz.
VSWR (MAX.) ❋	1.08 + .010 x FGHz.
INSERTION LOSS (dB MAX.) ❋	.045 dB x $\sqrt{FGHz}$.
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	250
RF LEAKAGE (MIN. dB DOWN)	100 dB - FGHz.
TEMPERATURE RATING (DEGREES CENTIGRADE)	−65° c TO +150° c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	500
INSULATION RESISTANCE (MIN. MEGOHMS)	2,500
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	6.0
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

❋ TERMINATED IN A 50 OHM LOAD

RoHS
COMPLIANT

REV.	DCN NO.	DATE	APP.
AA	13-1058	1/14/13	TS

DIMENSIONS ARE IN INCHES
TOLERANCES
DECIMALS: .X ±.030, .XX ±.010, .XXX ±.005
FRACTIONAL: ±1/64
ANGULAR: X° ±1°0', X° X ± 15'
SURFACE ROUGHNESS 63 √ MIL-STD 10.

dynawave INCORPORATED
HAVERHILL MA. 01835

DRAWN	TS	DATE	1/14/13
APPD	DC	DATE	1/14/13

TITLE: SMP MALE
2 HOLE MOUNT
STRAIGHT TERMINAL
FULL DETENT

CODE IDENT.	SHEET 1 OF 2	DWG. NO.
2J899		2152-0031-6259

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT

- MIN. AXIAL FORCE — 3.5 LBS.
- MIN. RADIAL TORQUE — N/A

CONNECTOR ENGAGEMENT FORCES

- INSERTION (MAX. LBS.) — 15.0
- WITHDRAWAL (MIN. LBS.) — 5.0

CONNECTOR DURABILITY (MIN. MATING) — 100

4. ENVIRONMENTAL

TEMPERATURE CYCLING	MIL–STD–202, METHOD 102, COND. C (–65 ° c TO + 165 °c)
SHOCK	MIL–STD–202, METHOD 213, COND. I (100 G's)
VIBRATION	MIL–STD–202, METHOD 204, COND. D (20 G's)
MOISTURE RESISTANCE	MIL–STD–202, METHOD 106, LESS STEP 7b
CORROSION	MIL–STD–202, METHOD 101, COND. B (48 HOURS)
BAROMETRIC PRESSURE (ALTITUDE)	MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (125 VRMS)

CONFIDENTIAL

5. MATERIAL

CONNECTOR BODY	STAINLESS STEEL PER ASTM A 582, TYPE 303, COND. A.
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196/B, 196M–03, COPPER ALLOY UNS C17300, TEMPER TD04.
INSULATOR	TEFLON PER ASTM D 1710–02, TYPE 1, GRADE 1, CLASS B.

6. FINISH

CONNECTOR BODY	PASSIVATE PER AMS 2700, TYPE 2, CLASS 4.
CENTER CONTACT	GOLD PER ASTM–B–488, TYPE I, GRADE C, CLASS 1.27 (.000050 MIN. THK.) OVER NICKEL PER SAE AMS QQ–N–290, CLASS 1 (.000050 MIN.) OVER COPPER PER AMS 2418 (.000010 MIN. THK.)
INSULATOR	N/A