SPECIFICATION CONTROL DRAWING





CONFIDENTIAL

1. MATING INTERFACE DIMENSIONS PER MIL-STD. 348A, Fig. 326.2 (SMP, PLUG, FULL DETENT)

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 18.0 GHz.
VSWR (MAX.) ❋	1.07 + .010 x FGHz.
INSERTION LOSS (dB MAX.) ❋	.050 dB x $\sqrt{FGHz}$.
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	250
RF LEAKAGE (MIN. dB DOWN)	100 dB - FGHz.
TEMPERATURE RATING (DEGREES CENTIGRADE)	−65° c TO +150° c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	500
INSULATION RESISTANCE (MIN. MEGOHMS)	5,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	4.0
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

❋ TERMINATED IN A 50 OHM LOAD

RoHS COMPLIANT

This Document contains proprietary and confidential information.

REV.	DCN NO.	DATE	APP.
AA	18-1176	2/8/18	TS

DIMENSIONS ARE IN INCHES
TOLERANCES

DECIMALS	FRACTIONAL	ANGULAR
.X ±.030 .XX ±.010 .XXX ±.005	±1/64	X° ±1°0' X° X' ±15'

SURFACE ROUGHNESS 63 √ MIL-STD 10.

dynawave INCORPORATED
HAVERHILL, MA. 01835

DRAWN	TS	DATE	2/8/18
APPROVED	DC	DATE	2/8/18

TITLE: SMP, PLUG
(FULL DETENT)
RIGHT ANGLE 2 HOLE FLANGE
FIELD REPLACEABLE

CODE IDENT.	SHEET 1 OF 2	DWG. NO.
2J899		2156-0881-6203

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT
- MAX.AXIAL FORCE — N/A
- MAX. RADIAL TORQUE — N/A

CENTER CONTACT AXIAL FORCES
- INSERTION (MAX. OUNCES) — 32.0
- WITHDRAWAL (MIN. OUNCES) — 1.0

CONNECTOR DURABILITY (MIN. CYCLES) — 100

ENGAGEMENT FORCES
- INSERTION (MAX.) — 15.0 LBS.
- WITHDRAWL (MIN.) — 5.0 LBS.

CONFIDENTIAL

4. ENVIRONMENTAL

TEMPERATURE CYCLING	MIL–STD–202, METHOD 102, COND. C (–65° c TO + 165° c)
SHOCK	MIL–STD–202, METHOD 213, COND. I (100 G's)
VIBRATION	MIL–STD–202, METHOD 204, COND. D (20 G's)
MOISTURE RESISTANCE	MIL–STD–202, METHOD 106, LESS STEP 7b
CORROSION	MIL–STD–202, METHOD 101, COND. B (48 HOURS)
BAROMETRIC PRESSURE (ALTITUDE)	MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (125 VRMS)

5. MATERIAL

CONNECTOR BODY AND PRESS SLEEVE	STAINLESS STEEL PER ASTM A 582, TYPE 303, COND. A
CONTACT	BERYLLIUM COPPER PER ASTM B196/B, 196M–03, COPPER ALLOY No. UNS–C17300, TEMPER TD04.
INSULATOR	TEFLON PER ASTM D 1710–02, TYPE 1, GRADE 1, CLASS B.

6. FINISH

CONNECTOR BODY AND PRESS SLEEVE	PASSIVATE PER AMS 2700, TYPE 2, CLASS 4.
CONTACT	GOLD PER ATSM B 488, TYPE 1, CODE C, CLASS 1.25 (.000050 MIN. THK.) OVER NICKEL PER SAE AMS QQ–N–290, CLASS 1 (.000050 MIN. THK.) OVER COPPER AMS 2418 (.000010 MIN. THK.)
INSULATOR	N/A