SPECIFICATION CONTROL DRAWING





MOUNTING PACKAGE DIMENSIONS

CONFIDENTIAL

1. MATING INTERFACE DIMENSIONS PER MIL-STD 348A, FIG. 321.1 (BMA, PLUG)
2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 26.5 GHz
VSWR (MAX.) ❋	SEE SHEET 3
INSERTION LOSS (dB MAX.)	
• BMA INTERFACE GAP (.000 to .015)	.035 dB x $\sqrt{FGHz}$
• BMA INTERFACE GAP (.016 to .030)	.060 dB x $\sqrt{FGHz}$
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	250
RF LEAKAGE (MIN. dB DOWN)	
• BMA INTERFACE BOTTOMED (.000 GAP)	100 dB – FGHz
• BMA INTERFACE GAP (.001 to .015)	90 dB – FGHz
• BMA INTERFACE GAP (.016 to .030)	75 dB – FGHz
TEMPERATURE RATING (DEGREES CENTIGRADE)	−65°c TO + 165°c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	750
INSULATION RESISTANCE (MIN. MEGOHMS)	10,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	6.0
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

❋ TERMINATED IN A 50 OHM LOAD

RoHS COMPLIANT

This Document contains proprietary and confidential information.

REV.	DCN NO.	DATE	APP.
–	1106	8/94	TS
A	1124	11/94	GL
AA	11-1969	11/1/11	TS
AB	13-2510	11/5/13	TS

DIMENSIONS ARE IN INCHES
TOLERANCES
DECIMALS .X ±.030, .XX ±.010, .XXX ±.005
FRACTIONAL ±1/64
ANGULAR X° ±1°, X° X' ±15'
SURFACE ROUGHNESS 63 √ MIL-STD 10.

DRAWN TS DATE 8/94

APPROVED TS DATE 8/94

CODE IDENT. 2J899

Sheet 1 of 3

dynawave INCORPORATED
HAVERHILL, MA. 01835

TITLE
BMA, PLUG
SCREW-IN
.020 DIA. STRAIGHT TERMINAL

DWG. NO. 2830-0031-6220

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT	
• MIN. AXIAL FORCE (BOTH)	4.5 LBS.
• MIN. RADIAL TORQUE	N/A
BMA ENGAGEMENT FORCES	
• INSERTION (MAX. OUNCES)	N/A
• WITHDRAWAL (MIN. OUNCES)	N/A
BMA DURABILITY (MIN. MATING)	1,000
RECOMMENDED MOUNTING TORQUE	7 – 11 IN./LBS.

RECOMMENDED TORQUE TOOL : 28-TORQUE-10

4. ENVIRONMENTAL

TEMPERATURE CYCLING	MIL–STD–202, METHOD 102, COND. C (–65 °c TO + 200 °c)
SHOCK	MIL–STD–202, METHOD 213, COND. I (100 G's)
VIBRATION	MIL–STD–202, METHOD 204, COND. D (20 G's)
MOISTURE RESISTANCE	MIL–STD–202, METHOD 106, LESS STEP 7b
CORROSION	MIL–STD–202, METHOD 101, COND. B (48 HOURS)
BAROMETRIC PRESSURE (ALTITUDE)	MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (250 VRMS)
HERMETICITY	1×10^{-8} cc/SEC.

CONFIDENTIAL

5. MATERIAL

CONNECTOR BODY	STAINLESS STEEL PER ASTM–A–582, TYPE 303, COND. A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM–B–196/B, 196M–03, COPPER ALLOY No. UNS–C17300, TEMPER TD04.
INSULATOR	TEFLON PER ASTM–D–1710–02, TYPE 1, GRADE 1, CLASS B.

6. FINISH

CONNECTOR BODY	PASSIVATE PER AMS–2700, TYPE 2, CLASS 4.
CENTER CONTACT	GOLD PER ASTM–B–488, TYPE I, CODE C, CLASS 1.27 (.000050 MIN. THK.) OVER NICKEL PER SAE–AMS–QQ–N–290 CLASS 1 (.000050 MIN. THK.) OVER COPPER PER AMS–2418 (.000010 MIN. THK.)
INSULATOR	N/A

SPECIFICATION CONTROL DRAWING







CONFIDENTIAL

dynawave INCORPORATED	Sheet 3 of 3	DWG. NO. 2830-0031-6220	REV. AB