SPECIFICATION CONTROL DRAWING



CONFIDENTIAL

1. MATING INTERFACE DIMENSIONS PER DYNAWAVE SPECIFICATION MD-31.

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 12.5 GHz.
VSWR (MAX.) ❁	1.10 + .015 x FGHz.
INSERTION LOSS (dB MAX.)	.04dB x $\sqrt{\text{FGHz}}$
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	125
RF LEAKAGE (MIN. dB DOWN)	N/A
TEMPERATURE RATING (DEGREES CENTIGRADE)	-65 ° c TO +165 ° c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	375
INSULATION RESISTANCE (MIN. MEGOHMS)	5,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	4.0
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

❁ TERMINATED IN A 50 OHM LOAD

REV.	DCN NO.	DATE	APP.
AA	03-1930		

DIMENSIONS ARE IN INCHES
TOLERANCES

DECIMALS	FRACTIONAL	ANGULAR
.X ±.030 .XX ±.010 .XXX ±.005	±1/64	X °±1 °D' X ° X' ± 15'

SURFACE ROUGHNESS 65 √ MIL-STD 10.

dynawave INCORPORATED
HAVERHILL, MA. 01835

DRAWN G.E. DATE 7/24/03

APPROVED DATE

TITLE
SMPM, MALE
(FULL DETENT)
SURFACE MOUNT

CODE IDENT.	SHEET 1 OF 2	DWG. NO.
2J899		3120-0390-6401

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT

- MAX. AXIAL FORCE — N/A
- MAX. RADIAL TORQUE — N/A

CONNECTOR ENGAGEMENT FORCES

- INSERTION (MAX. LBS.) — 4.5 LBS. MAX.
- WITHDRAWAL (MIN. LBS.) — 6.5 LBS. MIN.

CONNECTOR DURABILITY — 500

4. ENVIRONMENTAL

TEMPERATURE CYCLING	MIL–STD–202, METHOD 102, COND. C (–65 ° c TO + 165 °c)
SHOCK	MIL–STD–202, METHOD 213, COND. I (100 G's)
VIBRATION	MIL–STD–202, METHOD 204, COND. D (20 G's)
MOISTURE RESISTANCE	MIL–STD–202, METHOD 106, LESS STEP 7b
CORROSION	MIL–STD–202, METHOD 101, COND. B (48 HOURS)
BAROMETRIC PRESSURE (ALTITUDE)	MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (125 VRMS)

CONFIDENTIAL

5. MATERIAL

SHROUD	STAINLESS STEEL PER ASTM A 581, FREE MACHING TYPE 303, COND. A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B196–90, COPPER ALLOY NO. UNS C17300, TEMPER TD04.

6. FINISH

SHROUD	GOLD PER ATSM B 488, TYPE 1, CODE C, CLASS 1.25 (.000050 MIN. THK.) OVER NICKEL PER QQ–N–290 (.000150 MIN. THK.) OVER NICKEL (WOODS OF WATTS), (.000010 MIN. THK.)
CENTER CONTACT	GOLD PER ATSM B 488, TYPE I, CODE C, CLASS 2.5 (.000010 MIN. THK.) OVER NICKEL PER QQ–N–290, (.000050 MIN. THK.) OVER COPPER PER MIL–C–14550 (.000010 MIN. THK.)