SPECIFICATION CONTROL DRAWING



CONFIDENTIAL

1. MATING

INTERFACE DIMENSIONS PER MIL-STD-348A, Fig. 321.2 (BMA JACK).

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 18.0 GHz
VSWR (MAX.) *	1.05 + .005 x FGHz.
INSERTION LOSS (dB MAX.)	.030 dB x $\sqrt{FGHz}$
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	500
RF LEAKAGE (MIN. dB DOWN)	-100 dB - FGHz
TEMPERATURE RATING (DEGREES CENTIGRADE)	-65°c TO +165°c
DIELECTRIC WITHSTANDING VOLTAGE (MIN. VRMS)	1,000
INSULATION RESISTANCE (MIN. MEGOHMS)	5,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	2.0
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

* TERMINATED IN A 50 OHM LOAD

RoHS
COMPLIANT

This Document contains proprietary and confidential information.

REV.	DCN NO.	DATE	APP.
AA	16-1567	5/6/16	TS

DIMENSIONS ARE IN INCHES
TOLERANCES

DECIMALS	FRACTIONAL	ANGULAR
.X ± .030 .XX ± .010 .XXX ± .005	± 1/64	X ° ± 1° 0' X ° X' ± 15'

dynawave INCORPORATED
HAVERHILL, MA 01835

DRAWN TS DATE 5/6/16

APPROVED DC DATE 5/6/16

TITLE
BMA JACK
2 HOLE FLANGE
STRAIGHT TERMINAL

CODE IDENT. 2J899

SHEET 1 OF 2

DWG. NO. 6752-0031-6253

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT
- MAX.AXIAL FORCE — 4.5 LBS.
- MAX. RADIAL TORQUE — N/A

CENTER CONTACT AXIAL FORCES
- INSERTION (MAX. OUNCES) — 32.0
- WITHDRAWAL (MIN. OUNCES) — 2.0

CONNECTOR ENGAGEMENT/DISENGAGEMENT (MAX. IN. LBS.) — 3.0 LBS ENGAGE, 1.0 OZ DISENGAGE

CONNECTOR DURABILITY (MIN. CYCLES) — 500

RECOMMENDED MATING TORQUE — N/A

CONFIDENTIAL

4. ENVIRONMENTAL

TEMPERATURE CYCLING	MIL–STD–202, METHOD 102, COND. C (–65° c TO + 165° c)
SHOCK	MIL–STD–202, METHOD 213, COND. I (100 G's)
VIBRATION	MIL–STD–202, METHOD 204, COND. D (20 G's)
MOISTURE RESISTANCE	MIL–STD–202, METHOD 106, LESS STEP 7b
CORROSION	MIL–STD–202, METHOD 101, COND. B (48 HOURS)
BAROMETRIC PRESSURE (ALTITUDE)	MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (335 VRMS)

5. MATERIAL

BODY	STAINLESS STEEL PER ASTM–A–582, TYPE 303, COND. A
CENTER CONTACT AND SPRING FINGERS	BERYLLIUM COPPER PER ASTM–B–196/B 196M–03, COPPER ALLOY No. UNS–C17300, TEMPER TD04.
CENTER CONTACT HOOD	BRASS PER ASTM–B–16, TEMPER H02, ALLOY C36000.
INSULATOR	TEFLON PER ASTM–D–1710–02, TYPE 1, GRADE 1, CLASS B.

6. FINISH

BODY	PASSIVATE PER AMS 2700, TYPE 2, CLASS 4.
CENTER CONTACT ASSEMBLY AND SPRING FINGERS	GOLD PER ASTM–B–488, TYPE I, CODE C, CLASS 1.25 (.000050 MIN. THK.) OVER NICKEL PER SAE AMS QQ–N–290, CLASS 1 (.000050 MIN. THK.) OVER COPPER AMS 2418 (.000010 MIN. THK.)
INSULATOR	N/A