SPECIFICATION CONTROL DRAWING



CONFIDENTIAL

1. MATING — INTERFACE DIMENSIONS PER MIL-STD-348A, Fig. 321-2 (BMA, JACK)

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 26.5 GHz
VSWR (MAX.) ❋	SEE SHEET 3
INSERTION LOSS (dB MAX.)	
• BMA INTERFACE GAP (.000 TO .010)	.035 dB x $\sqrt{FGHz}$
• BMA INTERFACE GAP (.011 TO .020)	.050 dB x $\sqrt{FGHz}$
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	333
RF LEAKAGE (MIN. dB DOWN)	
• BMA INTERFACE BOTTOMED (.000 GAP)	100 dB – FGHz
• BMA INTERFACE GAP (.001 TO .010)	90 dB – FGHz.
• BMA INTERFACE GAP (.011 TO .020)	75 dB – FGHz.
TEMPERATURE RATING (DEGREES CENTIGRADE)	–65°c TO +165°c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	1,000
INSULATION RESISTANCE (MIN. MEGOHMS)	5,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	6.0
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

❋ TERMINATED IN A 50 OHM LOAD

RoHS
COMPLIANT

This Document contains proprietary and confidential information.

REV.	DCN NO.	DATE	APP.
AA	18-1142	1/29/18	TS

DIMENSIONS ARE IN INCHES
TOLERANCES

DECIMALS	FRACTIONAL	ANGULAR
.X ± .030 .XX ± .010 .XXX ± .005	± 1/64	X ° ± 1° 0' X ° X' ± 15'

dynawave INCORPORATED
HAVERHILL, MA 01835

DRAWN TS DATE 1/29/18

APPROVED DC DATE 1/29/18

TITLE
BMA, JACK
4 HOLE FLANGE
STRAIGHT TERMINAL

CODE IDENT. 2J899

Sheet 1 of 3

DWG. NO. 6754-0631-6203

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT
- MAX AXIAL FORCE — 4.5 LBS.
- MAX. RADIAL TORQUE — N/A

CENTER CONTACT AXIAL FORCES
- INSERTION (MAX. OUNCES) — 48.0
- WITHDRAWAL (MIN. OUNCES) — 2.0

CONNECTOR ENGAGEMENT/DISENGAGEMENT (MAX. IN. LBS.) — 2.0

CONNECTOR DURABILITY (MIN. CYCLES) — 500

RECOMMENDED MATING TORQUE — N/A

CONFIDENTIAL

4. ENVIRONMENTAL

TEMPERATURE CYCLING	MIL–STD–202, METHOD 102, COND. C (–65° c TO + 165° c)
SHOCK	MIL–STD–202, METHOD 213, COND. I (100 G's)
VIBRATION	MIL–STD–202, METHOD 204, COND. D (20 G's)
MOISTURE RESISTANCE	MIL–STD–202, METHOD 106, LESS STEP 7b
CORROSION	MIL–STD–202, METHOD 101, COND. B (48 HOURS)
BAROMETRIC PRESSURE (ALTITUDE)	MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (250 VRMS)

5. MATERIAL

BODY	STAINLESS STEEL PER ASTM A 582, TYPE 303, COND. A
CONTACTS AND SPRING FINGERS	BERYLLIUM COPPER PER ASTM B196/B 196M–03, COPPER ALLOY No. UNS–C17300, TEMPER TD04.
CENTER CONTACT HOOD	BRASS PER ASTM B16, TEMPER H02, ALLOY C36000.
INSULATOR	TEFLON PER ASTM D 1710–02, TYPE 1, GRADE 1, CLASS B.
O'RING	NITRILE (BUNA–N)

6. FINISH

BODY	PASSIVATE PER AMS 2700, TYPE 2, CLASS 4.
CONTACTS AND SPRING FINGERS	GOLD PER ASTM B 488, TYPE II, CODE C, CLASS 1.27 (.000050 MIN. THK.) OVER NICKEL PER SAE AMS QQ–N–290, CLASS 1, (.000050 MIN. THK.) OVER COPPER PER AMS 2418 (.000010 MIN. THK.)
INSULATOR AND O'RING	N/A

SPECIFICATION CONTROL DRAWING







CONFIDENTIAL

dynawave INCORPORATED	Sheet 3 of 3	DWG. NO. 6754-0631-6203	REV. AA