SPECIFICATION CONTROL DRAWING



CONFIDENTIAL

1. MATING NOT-APPLICABLE

2. ELECTRICAL

FREQUENCY RANGE GHz	DC TO 36.0 GHz.
VSWR (MAX.) ❋	1.05 + .006 x FGHz.
INSERTION LOSS (dB MAX.) ❋	.03 dB x $\sqrt{\text{FGHz.}}$
NOMINAL IMPEDANCE (OHMS)	50
VOLTAGE RATING (MAX. VRMS)	250
RF LEAKAGE (MIN. dB DOWN)	100 dB - FGHz.
TEMPERATURE RATING (DEGREES CENTIGRADE)	−65 ° c TO +165 ° c
DIELECTRIC WITHSTANDING VOLTAGE (MAX. VRMS)	750
INSULATION RESISTANCE (MIN. MEGOHMS)	10,000
CONTACT RESISTANCE	
• CENTER CONTACT (MAX. MILLIOHMS)	7.5
• OUTER CONTACT (MAX. MILLIOHMS)	2.0

❋ TERMINATED IN A 50 OHM LOAD

REV.	DCN NO.	DATE	APP.
–	1011	9/93	G.L.
A	1045	12/93	M.B.
B	1052	1/94	T.S.
C	1057	1/94	T.S.

DIMENSIONS ARE IN INCHES
TOLERANCES

DECIMALS	FRACTIONAL	ANGULAR
.X ± .030 .XX ± .010 .XXX ± .005	± 1/64	X ° ± 1 °0' X ° X' ± 15'

SURFACE ROUGHNESS 63 √ MIL-STD 10.

dynawave INCORPORATED
HAVERHILL, MA. 01835

DRAWN G.L. DATE 9/93

APPROVED DGG DATE 9/93

TITLE
DIRECT ATTACHMENT
.085 SEMI-RIGID CABLE
(2) HOLE FLANGE

CODE IDENT. 2J899

SHEET 1 OF 2

DWG. NO. 6952-8527-2763

SPECIFICATION CONTROL DRAWING

3. MECHANICAL

CAPTIVATION–CENTER CONTACT
- MAX. AXIAL FORCE — 6.0 LBS.
- MAX. RADIAL TORQUE — N/A

CENTER CONTACT AXIAL FORCES
- INSERTON (MAX. OUNCES) — 32.0
- WITHDRAWAL (MIN. OUNCES) — 1.5

CONNECTOR ENGAGEMENT/ DISENGAGEMENT (MAX. IN. LBS.) — N/A

CONNECTOR DURABILITY (MIN. CYCLES) — N/A

RECOMMENDED MATING TORQUE — N/A

4. ENVIRONMENTAL

TEMPERATURE CYCLING — MIL–STD–202, METHOD 102, COND. C (–65 ° c TO + 200 °c)

SHOCK —

VIBRATION — 0 G's)

MOISTURE RES — MIL–STD–202, METHOD 106, LESS STEP 7b

— MIL–STD–202, METHOD 101, COND. B (48 HOURS)

— MIL–STD–202, METHOD 105, COND. C (70,000 FT.) (190 VRMS)

CONFIDENTIAL

5. MATERIAL

CONNECTOR BODY	BRASS PER ASTM B36, TEMPER H02, ALLOY C36000
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B196–90, COPPER ALLOY No. UNS C17300, TEMPER TD04.
INSULATOR	TEFLON PER ASTM D 4894
EMI GASKET	SILVER PLATED ALUMINUM IN SILICONE

6. FINISH

CONNECTOR BODY	NICKEL PER MIL–P27418 (.000200 TO .000250 THK.) OVER COPPER PER MIL–C–14550 (.000010 TO .000025 THK.)
CENTER CONTACT	GOLD PER MIL–G–45204, TYPE II, GRADE C, CLASS 2 (.000010 MIN.) OVER NICKEL PER QQ–N–290, CLASS 1 (.00010 MIN.) OVER COPPER PER MIL–C–14550 (.000010 MIN.)
INSULATOR AND EMI GASKET	N/A